

Mitchell Industrial Tire Company, Inc.

SOLID SOLVER



RESILIENT




Manufactured in the U.S.A.


100% natural rubber compound delivers cut and abrasion resistance and generates less heat in operation giving longer life expectancy and low rolling resistance.

PERFORMANCE

COMFORT



TIRE LIFE



ENERGY SAVINGS



www.mitco.com



Compared to industry standards

TIRE SIZE	RIM SIZE	ACTUAL TIRE DIMENSIONS		TREAD WIDTH	TREAD DEPTH	AVG. WEARABLE HEIGHT	LOAD CAPACITY	
		OVERALL DIAMETER	OVERALL WIDTH				COUNTERBALANCED	
							LIFT TRUCKS	
	AT 6 MPH	AT 10 MPH						
(in)	(in)	(in)	(in)	(in)	(in)	(in)	(lbs)	(lbs)
4.00-6 (RIB)	6 X 3.25	10.5	4.0	2.9	0.11	1.0	--	595
4.00-8 (RIB)	8 X 3.75	16.4	4.8	4.2	0.13	1.8	--	2105
15x4.5-8*	8 X 3.0	14.5	4.3	3.8	0.50	1.4	1260	910
5.00-8	8 X 3.0	17.9	4.8	4.4	0.85	2.1	--	1935
5.00-8	8 X 3.25	17.9	4.8	4.4	0.85	2.1	--	2100
5.00-8 (RIB)	8 X 3.75	17.9	4.8	4.4	0.11	2.1	--	2420
16x6-8*	8 X 4.33	15.9	5.7	5.3	0.65	1.4	1310	1205
18x7-8*	8 X 4.33	18.1	6.5	5.5	0.64	2.1	3750	2715
6.00-9*	9 X 4.0	21.0	5.4	5.1	0.59	2.5	4230	3065
21x8-9*	9 X 6.0	19.8	7.3	6.7	0.75	2.3	6190	4480
6.50-10*	10 X 5.0	23.0	6.7	6.1	0.59	2.7	5810	4210
23x9-10*	10 X 6.5	23.0	8.1	7.5	0.87	2.7	7525	5450
23x10-12*	12 X 8.0	23.0	9.5	8.8	0.63	2.3	8820	6385
200x50-10*	10 X 6.5	17.0	7.9	7.4	0.75	1.5	9530	6900
7.00-12*	12 X 5.0	26.1	6.8	6.3	0.62	2.9	6640	4810
27x10-12*	12 X 8.0	26.0	9.5	8.7	0.87	2.9	8598	7804
7.00-15	15 X 5.5	29.1	7.6	7.0	0.69	2.9	7905	5725
7.50-15	15 X 5.5	29.5	8.0	7.2	0.59	2.9	8630	6250
7.50-15	15 X 6.5	29.5	8.0	7.2	0.59	2.9	10195	7385
6.50-16	16 X 5.5	29.5	6.9	6.1	0.63	2.8	6415	4645
7.50-16	16 X 5.5	31.3	8.0	6.7	0.69	3.1	8615	6240
8.00-16	16 X 5.5	32.5	8.1	7.3	0.63	3.4	8800	6375
8.15-15 (28X9-15)*	15 X 7.0	28.0	8.7	8.0	0.63	2.6	9000	6520

* Available in EF Click Type



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

TIRE SIZE	RIM SIZE	ACTUAL		TREAD WIDTH	TREAD DEPTH	AVG. WEARABLE HEIGHT	LOAD CAPACITY	
		TIRE DIMENSIONS					COUNTERBALANCED LIFT TRUCKS	
		OVERALL DIAMETER	OVERALL WIDTH					
								AT 6 MPH
	(in)	(in)	(in)	(in)	(in)	(in)	(lbs)	(lbs)
250-15*	15 X 7.0	29.0	9.9	8.7	0.63	2.9	9615	6960
250-15*	15 X 7.5	29.0	9.9	8.7	0.63	2.9	10300	7460
28x12.5-15*	15 X 9.75	27.8	12.0	10.9	1.13	2.6	10085	7300
8.25-15*	15 X 6.5	32.5	8.6	8.0	0.69	3.6	10875	7875
300-15*	15 X 8.0	32.3	10.8	9.6	0.69	3.5	13190	9550
10.00-20	20 X 7.0	39.3	9.8	8.7	1.25	3.9	16800	12200
10.00-20	20 X 7.5	39.3	9.8	8.7	1.25	3.9	16900	12200
10.00-20	20 X 8.0	39.3	9.8	8.7	1.25	3.9	17015	12320
12.00-20	20 X 8.0	42.3	10.5	8.9	1.25	4.5	18605	13475
12.00-20	20 X 8.5	42.3	10.5	8.9	1.25	4.5	18605	13475

* Available in EF Click Type

FLAT, BROAD PROFILE

- Built for stability and safety

SPECIALLY DESIGNED TIRE LUGS

- Designed for grip, ride and braking for operator comfort and safety



100% NATURAL RUBBER COMPOUND

- Delivers cut and abrasion resistance and generates less heat in operation giving longer life expectancy and low rolling resistance.



AVAILABLE IN NON-MARKING COMPOUND

Problem solving compounds and specialty sizes available with a 2 week lead time

MANUFACTURED IN THE U.S.A.

Chattanooga, Tennessee

EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)



S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

WARRANTIES

All products sold by MITCO are guaranteed to be free from defects in workmanship and materials. Any product found by us to have such a defect will be replaced or a reasonable adjustment or allowance will be made against the purchase of a new product, within our discretion. All other costs involved, including, but not limited to, labor, freight, service, and taxes are to be borne by the buyer. The buyer agrees that replacement or adjustment, as aforesaid, shall be the exclusive remedy and that MITCO shall not in any event be held liable for any special, indirect, or consequential damages. MITCO makes no other warranty, expressed or implied and specifically excludes any and all warranties of MERCHANTABILITY and FITNESS for a particular purpose.

MITCHELL INDUSTRIAL TIRE CO., INC.

Corporate Offices and Main Production Facilities

2915 Eighth Avenue

P.O. Box 9527

Chattanooga, Tennessee 37407

Chattanooga, Tennessee 37407

Toll Free Sales: (800) 251-7226

Sales: (423) 698-4283/Fax: (423)697-7143

Northeast Distribution Center

7900 Radcliffe Street, Building 103A

Bristol, PA 19007

Toll Free Sales: (800) 251-7226

West Coast Sales and Distribution Center

12423 East Florence Avenue, Suite C

Santa Fe Springs, California 90670

Toll Free Sales: (800) 648-2699

Sales: (562) 941-1263/Fax: (562) 941-3766



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

WEST COAST

(800) 648-2699

WWW.MITCO.COM

S I N C E 1 9 5 3