

Mitchell Industrial Tire Company, Inc.

SUPER SOLID



PRESS ON



Manufactured in the U.S.A.


100% natural rubber compound delivers cut and abrasion resistance and generates less heat in operation giving longer life expectancy and low rolling resistance.

www.mitco.com



PERFORMANCE

COMFORT



TIRE LIFE



ENERGY SAVINGS



Compared to industry standards

TIRE SIZE	RIM SIZE	ACTUAL		TREAD WIDTH	TREAD DEPTH LUG/IDL	AVG. WEARABLE HEIGHT	LOAD CAPACITY	
		TIRE DIMENSIONS					COUNTERBALANCED	
		OVERALL DIAMETER	OVERALL WIDTH				LIFT TRUCKS	
							AT 6 MPH	AT 10 MPH
	(in)	(in)	(in)	(in)	(in)	(in)	(lbs)	(lbs)
8½x4x4 **	4x4	8.5	4	2.80	NA	0.94	1430	1260
9x5x5 **	5x5	9	5	3.94	NA	0.81	1960	1740
10x3x6¼ **	3x6¼	10	3	2.01	NA	0.75	1100	970
10x3½x6 **	3½x6	10	3.5	2.44	NA	0.81	1350	1190
10x4x6¼ **	4x6¼	10	4	3.03	NA	0.75	1600	1420
10x4x6½ **	4x6½	10	4	3.07	NA	0.69	1590	1400
10x4¾x6½	4¾x6½	10	4.75	3.86	NA	0.69	1950	1730
10x5x6¼ **	5x6¼	10	5	4.02	NA	0.75	2100	1860
10x5x6½ *	5x6½	10	5	4.09	.74/.69	0.69	2070	1840
10x6x6¼ **	6x6¼	10	6	5.04	NA	0.75	2600	2300
10x6x6½ **	6x6½	10	6	5.12	NA	0.69	2560	2270
10x7x6¼ **	7x6¼	10	7	6.02	NA	0.75	3100	2750
10½x5x5	5x5	10.5	5	3.54	.71/NA	1.19	2250	1990
10½x5x6½ *	5x6½	10.5	5	3.94	.72/.70	0.81	2200	1950
10½x6x5	6x5	10.5	6	4.57	.74/NA	1.19	2860	2530
10½x6x6½	6x6½	10.5	6	4.96	.77/NA	0.81	2740	2420
10½x7x6½ **	7x6½	10.5	7	5.98	NA	0.81	3270	2890
12x3½x8 **	3½x8	12	3.5	2.44	NA	0.81	1550	1370
12x3½x10 **	3½x10	12	3.5	2.99	NA	0.31	1360	1200
12x4x8 **	4x8	12	4	2.95	NA	0.81	1840	1630
12x4½x8 **	4½x8	12	4.5	3.46	NA	0.81	2140	1890
12x5x8 **	5x8	12	5	3.94	NA	0.81	2430	2150
12x5½x8 **	5½x8	12	5.5	4.45	NA	0.81	2730	2410

* Available in IDL, Traction and Smooth tread design

** Available in Smooth tread design only



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

TIRE SIZE	RIM SIZE	ACTUAL TIRE DIMENSIONS		TREAD WIDTH	TREAD DEPTH LUG/IDL	AVG. WEARABLE HEIGHT	LOAD CAPACITY	
		OVERALL DIAMETER	OVERALL WIDTH				COUNTERBALANCED	
							LIFT TRUCKS	
	AT 6 MPH	AT 10 MPH						
(in)	(in)	(in)	(in)	(in)	(in)	(in)	(lbs)	(lbs)
12x6½x8 **	6½x8	12	6.5	5.47	NA	0.81	3320	2940
13½x4½x8 *	4½x8	13.5	4.5	3.03	.76/.71	1.19	2350	2080
13½x5½x8 *	5½x8	13.5	5.5	4.06	.72/.67	1.19	3080	2730
13½x6½x8 **	6½x8	13.5	6.5	5.08	NA	1.19	3810	3370
13x3½x8 **	3½x8	13	3.5	2.17	NA	1.06	1610	1430
13x4½x8	4½x8	13	4.5	3.19	NA	1.06	2300	2030
14x4½x8 *	4½x8	14	4.5	2.91	.74/.73	1.31	2390	2120
14x5x10 **	5x10	14	5	3.94	NA	0.81	2730	2420
15x3½x11¼ **	3½x11¼	15	3.5	2.52	NA	0.75	1830	1620
15x4x11¼ **	4x11¼	15	4	3.03	NA	0.75	2170	1920
15x5x11¼ *	5x11¼	15	5	4.02	.76/.73	0.75	2850	2520
15x6x11¼	6x11¼	15	6	5.04	.77/NA	0.75	3530	3120
15x7x11¼ **	7x11¼	15	7	6.02	NA	0.75	4210	3720
15x8x11¼ **	8x11¼	15	8	7.05	NA	0.75	4890	4320
15x9x11¼ **	9x11¼	15	9	8.07	NA	0.75	5570	4920
15½x5x10	5x10	15.5	5	3.54	.76/NA	1.19	3010	2670
15½x6x10	6x10	15.5	6	4.57	.73/NA	1.19	3820	3380
16x3½x12⅝ **	3½x12⅝	16	3.5	2.48	NA	0.78	1920	1700
16x4x12⅝ **	4x12⅝	16	4	2.99	NA	0.78	2280	2020
16x4½x10½	4½x10½	16	4.5	3.03	.76/NA	1.19	2670	2360
16x5x10½ *	5x10½	16	5	3.54	.71/.70	1.19	3090	2730
16x6x10½ *	6x10½	16	6	4.57	.68/.67	1.19	3920	3460
16x7x10½ *	7x10½	16	7	5.55	.69/.71	1.19	4750	4200

* Available in IDL, Traction and Smooth tread design

** Available in Smooth tread design only



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

TIRE SIZE	RIM SIZE	ACTUAL TIRE DIMENSIONS		TREAD WIDTH	TREAD DEPTH LUG/IDL	AVG. WEARABLE HEIGHT	LOAD CAPACITY		
							COUNTERBALANCED LIFT TRUCKS		
		OVERALL DIAMETER	OVERALL WIDTH					AT 6 MPH	AT 10 MPH
	(in)	(in)	(in)	(in)	(in)	(in)	(lbs)	(lbs)	
16¼x4x11¼	4x11¼	16.25	4	2.68	.70/NA	1.06	2310	2040	
16¼x5x11¼ *	5x11¼	16.25	5	3.70	.70/.71	1.06	3120	2760	
16¼x6x11¼ *	6x11¼	16.25	6	4.69	.73/.70	1.06	3930	3480	
16¼x7x11¼ *	7x11¼	16.25	7	5.71	.73/.69	1.06	4740	4190	
17x5x12⅞	5x12⅞	17	5	3.70	.73/NA	1.03	3220	2850	
17x6x12⅞	6x12⅞	17	6	4.72	.72/NA	1.03	4050	3580	
18x5x12⅞ *	5x12⅞	18	5	3.46	.69/.94	1.28	3360	2980	
18x5x14 **	5x14	18	5	3.94	NA	0.81	3300	2920	
18x6x12⅞ *	6x12⅞	18	6	4.45	.63/.92	1.28	4290	3800	
18x7x12⅞ *	7x12⅞	18	7	5.47	.69/.69	1.28	5220	4620	
18x8x12⅞ *	8x12⅞	18	8	6.50	.97/.67	1.28	6150	5440	
18x8x14 **	8x14	18	8	6.97	NA	0.81	5680	5030	
18x9x12⅞ *	9x12⅞	18	9	7.48	.75/.68	1.28	7080	6270	
18x9x14 **	9x14	18	9	7.99	NA	0.81	6480	5730	
18x10x12⅞ **	10x12⅞	18	10	8.50	NA	1.28	8010	7090	
18x12x14 **	12x14	18	12	11.02	NA	0.81	8900	7870	
20x3½x16 **	3½x16	20	3.5	2.44	NA	0.81	2270	2010	
20x5x16 **	5x16	20	5	3.94	NA	0.81	3570	3160	
20x6x16	6x16	20	6	4.96	.69/NA	0.81	4440	3920	
20x7x16 **	7x16	20	7	5.98	NA	0.81	5300	4690	
20x8x15	8x15	20	8	6.73	.67/NA	1.06	6480	5730	
20x8x16	8x16	20	8	6.97	.70/NA	0.81	6170	5460	
20x9x15	9x15	20	9	7.72	.69/NA	1.06	7430	6570	

* Available in IDL, Traction and Smooth tread design

** Available in Smooth tread design only



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

TIRE SIZE	RIM SIZE	ACTUAL		TREAD WIDTH	TREAD DEPTH LUG/IDL	AVG. WEARABLE HEIGHT	LOAD CAPACITY	
		TIRE DIMENSIONS					COUNTERBALANCED	
		OVERALL DIAMETER	OVERALL WIDTH				LIFT TRUCKS	
							AT 6 MPH	AT 10 MPH
	(in)	(in)	(in)	(in)	(in)	(in)	(lbs)	(lbs)
20x9x16 **	9x16	20	9	7.99	NA	0.81	7030	6220
20½x7x17¾ **	7x17¾	20.5	7	6.30	NA	0.50	4850	4290
21x5x15	5x15	21	5	3.43	.70/NA	1.31	3770	3330
21x6x15 *	6x15	21	6	4.41	.72/.70	1.31	4820	4270
21x7x15 *	7x15	21	7	5.43	.66/.70	1.31	5870	5200
21x8x15 *	8x15	21	8	6.46	.66/.68	1.31	6930	6130
21x9x15 *	9x15	21	9	7.44	.66/.69	1.31	7980	7060
22x5x16	5x16	22	5	3.43	.72/NA	1.31	3900	3450
22x6x16	6x16	22	6	4.41	.71/NA	1.31	4990	4420
22x6x17¾	6x17¾	22	6	4.88	.74/NA	0.88	4820	4260
22x7x16	7x16	22	7	5.43	.71/NA	1.31	6080	5380
22x7x17¾	7x17¾	22	7	5.91	.74/NA	0.88	5770	5100
22x8x16 *	8x16	22	8	6.46	.73/.99	1.31	7170	6340
22x9x16 *	9x16	22	9	7.44	.73/1.01	1.31	8260	7310
22x10x16 **	10x16	22	10	8.46	NA	1.31	9350	8270
22x10x17¾ **	10x17¾	22	10	8.94	NA	0.88	8630	7630
22x12x16 *	12x16	22	12	10.47	.72/.69	1.31	11530	10200
22x12x17¾ **	12x17¾	22	12	10.94	NA	0.88	10540	9320
22x14x16 **	14x16	22	14	12.52	NA	1.31	13710	12130
22x14x17¾**	14x17¾	22	14	12.99	NA	0.88	12440	11010
22x16x16 **	16x16	22	16	14.53	NA	1.31	15890	14050
24x3½x20 **	3½x20	24	3.5	2.44	NA	0.81	2600	2300
24x4x20 **	4x20	24	4	2.95	NA	0.81	3100	2740

* Available in IDL, Traction and Smooth tread design

** Available in Smooth tread design only



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

TIRE SIZE	RIM SIZE	ACTUAL		TREAD WIDTH	TREAD DEPTH LUG/IDL	AVG. WEARABLE HEIGHT	LOAD CAPACITY	
		TIRE DIMENSIONS					COUNTERBALANCED LIFT TRUCKS	
		OVERALL DIAMETER	OVERALL WIDTH					
								AT 6 MPH
	(in)	(in)	(in)	(in)	(in)	(in)	(lbs)	(lbs)
24x7x20 **	7x20	24	7	5.98	NA	0.81	6080	5380
26x5x20	5x20	26	5	3.43	.71/NA	1.31	4420	3910
26x7x20	7x20	26	7	5.43	.73/NA	1.31	6890	6100
26x8x20 **	8x20	26	8	6.46	NA	1.31	8130	7190
28x7x22	7x22	28	7	5.43	.71/NA	1.31	7290	6450
28x10x22 **	10x22	28	10	8.46	NA	1.31	11200	9910
28x12x22 *	12x22	28	12	10.47	NA/.75	1.31	13820	12220
28x14x22 **	14x22	28	14	12.52	NA	1.31	16430	14530
28x16x22 **	16x22	28	16	14.53	NA	1.31	19040	16840

* Available in IDL, Traction and Smooth tread design

** Available in Smooth tread design only

FLAT, BROAD PROFILE

- Built for stability and safety

INDUSTRIAL DEEP TIRE LUGS

- Designed for grip, ride and braking for operator comfort and safety



100% NATURAL RUBBER COMPOUND

- Delivers cut and abrasion resistance and generates less heat in operation giving longer life expectancy and low rolling resistance.

AVAILABLE IN SMOOTH, MILITARY LUG, IDL, & NON-MARKING COMPOUND



Problem solving compounds and specialty sizes available with a 2 week lead time

MANUFACTURED IN THE U.S.A.

Chattanooga, Tennessee

EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

NOTES:

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

MANUFACTURED IN THE U.S.A.

Chattanooga, Tennessee



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

S I N C E 1 9 5 3

WEST COAST

(800) 648-2699

WWW.MITCO.COM

WARRANTIES

All products sold by MITCO are guaranteed to be free from defects in workmanship and materials. Any product found by us to have such a defect will be replaced or a reasonable adjustment or allowance will be made against the purchase of a new product, within our discretion. All other costs involved, including, but not limited to, labor, freight, service, and taxes are to be borne by the buyer. The buyer agrees that replacement or adjustment, as aforesaid, shall be the exclusive remedy and that MITCO shall not in any event be held liable for any special, indirect, or consequential damages. MITCO makes no other warranty, expressed or implied and specifically excludes any and all warranties of MERCHANTABILITY and FITNESS for a particular purpose.

MITCHELL INDUSTRIAL TIRE CO., INC.

Corporate Offices and Main Production Facilities

2915 Eighth Avenue

P.O. Box 9527

Chattanooga, Tennessee 37407

Chattanooga, Tennessee 37407

Toll Free Sales: (800) 251-7226

Sales: (423) 698-4283/Fax: (423)697-7143

Northeast Distribution Center

7900 Radcliffe Street, Building 103A

Bristol, PA 19007

Toll Free Sales: (800) 251-7226

West Coast Sales and Distribution Center

12423 East Florence Avenue, Suite C

Santa Fe Springs, California 90670

Toll Free Sales: (800) 648-2699



EAST COAST

(800) 251-7226

(423) 697-7143 (FAX)

WEST COAST

(800) 648-2699

WWW.MITCO.COM

S I N C E 1 9 5 3